




400 V

MONO-BLOCK LOW NOX GAS BRANDER



Type	Ketel capaciteit (93% rendement)			Brander belasting		Control		Gas aansluitdruk		Max rookgaszijdige weerstand		Motor / drive power		Regelbereik		Verbruik			Max. Hoogte		Gas	Voeding
	kCal	HP	kW	kW	MMBTU	Gas	Olie	mbar	PSI	mbar	"wc	kW	HP	Gas	Olie	Gas m3	Gas ft3	Olie(kg/h)	mtr	ft		
VG1s-100	1.000.000	-	1163	1250	-	Modulerend	-	100-300	-	10	-	2,2	-	1:5	-	142	-	-	500	-	NG**	3x400V/50Hz***
VG1s-150	1.500.000	-	1745	1875	-	Modulerend	-	100-300	-	10	-	4,0	-	1:5	-	213	-	-	500	-	NG**	3x400V/50Hz***
VG1s-200	2.000.000	-	2326	2500	-	Modulerend	-	100-300	-	10	-	4,0	-	1:5	-	284	-	-	500	-	NG**	3x400V/50Hz***
VG1s-250	2.500.000	-	2908	3125	-	Modulerend	-	100-300	-	10	-	5,5	-	1:5	-	355	-	-	500	-	NG**	3x400V/50Hz***
VG1s-300	3.000.000	-	3489	3750	-	Modulerend	-	100-300	-	12	-	7,5	-	1:6	-	426	-	-	500	-	NG**	3x400V/50Hz***
VG1s-350	3.500.000	-	4071	4375	-	Modulerend	-	100-300	-	12	-	7,5	-	1:6	-	487	-	-	500	-	NG**	3x400V/50Hz***
VG1s-400	4.000.000	-	4652	5000	-	Modulerend	-	100-300	-	12	-	11,0	-	1:6	-	568	-	-	500	-	NG**	3x400V/50Hz***
VG1s-450	4.500.000	-	5234	5625	-	Modulerend	-	100-300	-	12	-	11,0	-	1:6	-	639	-	-	500	-	NG**	3x400V/50Hz***
VG1s-500	5.000.000	-	5815	6250	-	Modulerend	-	100-300	-	12	-	15,0	-	1:7	-	710	-	-	500	-	NG**	3x400V/50Hz***
VG1s-600	6.000.000	-	6978	7500	-	Modulerend	-	100-300	-	13	-	18,5	-	1:7	-	852	-	-	500	-	NG**	3x400V/50Hz***
VG1s-700	7.000.000	-	8141	8750	-	Modulerend	-	200-300	-	14	-	22	-	1:8	-	994	-	-	500	-	NG**	3x400V/50Hz***
VG1s-800	8.000.000	-	9304	10000	-	Modulerend	-	300	-	15	-	30	-	1:8	-	1136	-	-	500	-	NG**	3x400V/50Hz***
VG1s-1000	10.000.000	-	11630	12500	-	Modulerend	-	300	-	15	-	37	-	1:10	-	1420	-	-	500	-	NG**	3x400V/50Hz***
VG1s-1250	12.000.000	-	13956	15000	-	Modulerend	-	300	-	15	-	45	-	1:10	-	1704	-	-	500	-	NG**	3x400V/50Hz***