




# 480 V

MONO-BLOCK LOW NOx GAS BRANDER



Type	Kotel capaciteit (93% rendement)			Brander belasting		Control		Gas aansluitdruk		Max rookgaszijdige weerstand		Motor / drive power		Regelbereik		Verbruik			Max. Hoogte		Gas	Voeding
	kCal	HP	kW	kW	MMBTU	Gas	Olie	mbar	PSI	mbar	"wc	kW	HP	Gas	Olie	Gas m <sup>3</sup>	Gas ft <sup>3</sup>	Olie(kg/h)	mtr	ft		
VG1s-100	1.000.000	119	1163	1250	4	Modulerend	-	100-300	1,45-4,35	10	4,0	2,2	3,0	1,5	-	142	5015	-	500	1640	NG**	3x480V/60Hz***
VG1s-150	1.500.000	178	1743	1875	6	Modulerend	-	100-300	1,45-4,35	10	4,0	4,0	5,4	1,5	-	213	7522	-	500	1640	NG**	3x480V/60Hz***
VG1s-200	2.000.000	237	2326	2500	9	Modulerend	-	100-300	1,45-4,35	10	4,0	4,0	5,4	1,5	-	284	10079	-	500	1640	NG**	3x480V/60Hz***
VG1s-250	2.500.000	296	2908	3125	11	Modulerend	-	100-300	1,45-4,35	10	4,0	5,5	7,5	1,5	-	355	12537	-	500	1640	NG**	3x480V/60Hz***
VG1s-300	3.000.000	356	3489	3750	13	Modulerend	-	100-300	1,45-4,35	12	4,8	7,5	10,2	1,6	-	426	15044	-	500	1640	NG**	3x480V/60Hz***
VG1s-350	3.500.000	415	4071	4375	15	Modulerend	-	100-300	1,45-4,35	12	4,8	7,5	10,2	1,6	-	487	17198	-	500	1640	NG**	3x480V/60Hz***
VG1s-400	4.000.000	474	4652	5000	17	Modulerend	-	100-300	1,45-4,35	12	4,8	11,0	15,0	1,6	-	568	20059	-	500	1640	NG**	3x480V/60Hz***
VG1s-450	4.500.000	534	5234	5625	19	Modulerend	-	100-300	1,45-4,35	12	4,8	11,0	15,0	1,6	-	639	22566	-	500	1640	NG**	3x480V/60Hz***
VG1s-500	5.000.000	593	5815	6250	21	Modulerend	-	100-300	1,45-4,35	12	4,8	15,0	20,4	1,7	-	710	25073	-	500	1640	NG**	3x480V/60Hz***
VG1s-600	6.000.000	711	6978	7500	26	Modulerend	-	100-300	1,45-4,35	13	5,2	18,5	25,2	1,7	-	852	30088	-	500	1640	NG**	3x480V/60Hz***
VG1s-700	7.000.000	830	8141	8750	30	Modulerend	-	200-300	2,90-4,35	14	5,6	22	29,5	1,8	-	994	35103	-	500	1640	NG**	3x480V/60Hz***
VG1s-800	8.000.000	948	9304	10000	34	Modulerend	-	300	4,35	15	6,0	30	40,8	1,8	-	1136	40117	-	500	1640	NG**	3x480V/60Hz***
VG1s-1000	10.000.000	1186	11630	12500	43	Modulerend	-	300	4,35	17	6,8	37	50,4	1:10	-	1420	50147	-	500	1640	NG**	3x480V/60Hz***
VG1s-1250	12.000.000	1423	13956	15000	51	Modulerend	-	300	4,35	17	6,8	45	61,2	1:10	-	1704	60176	-	500	1640	NG**	3x480V/60Hz***