



480 V

MONO-BLOCK MODULEREND OLIE BRANDER
OLIE 100% MODULEREND



Type	Kleur capaciteit (10% rendement)			Brandert belasting		Control	Gas aansluitdruk		Max rookgasdruk waartoe		Motor / drive power		Regelruimte		Verbruik			Max. hoogte		Gas	Voeding	
	kcal	HP	kW	kW	MPELU		Gas	Olief	mbar	PSI	mbar	°C	kW	HP	Gas	Olief	Gas m3	Gas P3	Olief(kg/h)			mtr
V016-100	1.500.000	119	1163	1250	4	-	Modulerend	-	-	10	4,0	2,2	3,0	-	1,5	-	-	169	500	1640	-	34480V/50Hz***
V016-150	1.500.000	178	1745	1875	6	-	Modulerend	-	-	10	4,0	4,0	5,4	-	1,5	-	-	158	500	1640	-	34480V/50Hz***
V016-200	2.000.000	237	2336	2500	9	-	Modulerend	-	-	10	4,0	4,0	5,4	-	1,5	-	-	210	500	1640	-	34480V/50Hz***
V016-250	2.500.000	296	2908	3125	11	-	Modulerend	-	-	10	4,0	5,5	7,5	-	1,5	-	-	263	500	1640	-	34480V/50Hz***
V016-300	3.000.000	355	3488	3750	13	-	Modulerend	-	-	12	4,8	7,5	10,2	-	1,5	-	-	315	500	1640	-	34480V/50Hz***
V016-350	3.500.000	415	4071	4375	15	-	Modulerend	-	-	12	4,8	7,5	10,2	-	1,5	-	-	368	500	1640	-	34480V/50Hz***
V016-400	4.000.000	474	4652	5000	17	-	Modulerend	-	-	12	4,8	11,0	15,0	-	1,5	-	-	420	500	1640	-	34480V/50Hz***
V016-450	4.500.000	534	5234	5575	19	-	Modulerend	-	-	12	4,8	11,0	15,0	-	1,5	-	-	473	500	1640	-	34480V/50Hz***
V016-500	5.000.000	593	5815	6250	21	-	Modulerend	-	-	12	4,8	15,0	20,4	-	1,5	-	-	525	500	1640	-	34480V/50Hz***
V016-600	6.000.000	711	6978	7500	26	-	Modulerend	-	-	13	5,2	18,5	25,2	-	1,5	-	-	630	500	1640	-	34480V/50Hz***
V016-700	7.000.000	830	8144	8750	30	-	Modulerend	-	-	14	5,6	21	29,8	-	1,5	-	-	735	500	1640	-	34480V/50Hz***
V016-800	8.000.000	948	9304	10000	34	-	Modulerend	-	-	15	6,0	30	40,8	-	1,5	-	-	840	500	1640	-	34480V/50Hz***
V016-1000	10.000.000	1186	11630	12500	43	-	Modulerend	-	-	15	6,0	37	50,4	-	1,5	-	-	1050	500	1640	-	34480V/50Hz***
V016-1250	12.000.000	1423	13994	15000	51	-	Modulerend	-	-	15	6,0	45	61,2	-	1,5	-	-	1261	500	1640	-	34480V/50Hz***