




575 V

DUO-BLOCK LOW NOX GAS BRANDER



Type	Ketel capaciteit (93% rendement)			Brander belasting		Control		Gas aansluitdruk		Max rookgaszijde weerstand			Motor / drive power		Regelbereik		Verbruik		Max. Hoogte		Gas	Voeding
	kCal	HP	kW	kW	MHMTU	Gas	Olie	mbar	PSI	mbar	°w	kW	HP	Gas	Olie	Gas m3	Gas l/h	Oil	Oil (kg/h)	mtr		
VGB-100	1.000.000	119	116,3	1250	4	Modularend	-	100-300	1,45-4,35	10	4,0	2,2	3,0	1:5	-	142	5015	-	500	1640	NG**	3x575V/60Hz***
VGB-150	1.500.000	178	174,5	1875	6	Modularend	-	100-300	1,45-4,35	10	4,0	4,0	5,4	1:5	-	213	7522	-	500	1640	NG**	3x575V/60Hz***
VGB-200	2.000.000	237	232,6	2500	9	Modularend	-	100-300	1,45-4,35	10	4,0	4,0	5,4	1:5	-	284	10029	-	500	1640	NG**	3x575V/60Hz***
VGB-250	2.500.000	296	290,8	3125	11	Modularend	-	100-300	1,45-4,35	10	4,0	5,5	7,5	1:5	-	355	12537	-	500	1640	NG**	3x575V/60Hz***
VGB-300	3.000.000	396	389	3750	15	Modularend	-	100-300	1,45-4,35	12	4,8	7,5	10,2	1:6	-	446	15044	-	500	1640	NG**	3x575V/60Hz***
VGB-350	3.500.000	415	407,1	4375	15	Modularend	-	100-300	1,45-4,35	12	4,8	7,5	10,2	1:6	-	487	17198	-	500	1640	NG**	3x575V/60Hz***
VGB-400	4.000.000	474	465,2	5000	17	Modularend	-	100-300	1,45-4,35	12	4,8	11,0	15,0	1:6	-	568	20059	-	500	1640	NG**	3x575V/60Hz***
VGB-450	4.500.000	534	524	5625	19	Modularend	-	100-300	1,45-4,35	12	4,8	11,0	15,0	1:6	-	639	22566	-	500	1640	NG**	3x575V/60Hz***
VGB-500	5.000.000	593	581,5	6250	21	Modularend	-	100-300	1,45-4,35	12	4,8	15,0	20,4	1:7	-	710	25073	-	500	1640	NG**	3x575V/60Hz***
VGB-600	6.000.000	711	697,8	7500	26	Modularend	-	100-300	1,45-4,35	13	5,2	18,5	25,2	1:7	-	852	30088	-	500	1640	NG**	3x575V/60Hz***
VGB-700	7.000.000	830	814,1	8750	30	Modularend	-	200-300	2,90-4,35	14	5,6	22	29,9	1:8	-	994	35103	-	500	1640	NG**	3x575V/60Hz***
VGB-800	8.000.000	948	930,4	10000	34	Modularend	-	300	4,35	15	6,0	30	40,8	1:8	-	1136	40117	-	500	1640	NG**	3x575V/60Hz***
VGB-1000	10.000.000	1186	1163,0	12500	43	Modularend	-	300	4,35	15	6,0	37	50,4	1:10	-	1420	50147	-	500	1640	NG**	3x575V/60Hz***
VGB-1250	12.000.000	1423	1395,6	15000	51	Modularend	-	300	4,35	15	6,0	45	61,2	1:10	-	1704	60176	-	500	1640	NG**	3x575V/60Hz***
VGB-1500	15.000.000	1779	1744,8	18750	64	Modularend	-	300	4,35	15	6,0	55	74,8	1:10	-	2130	75220	-	500	1640	NG**	3x575V/60Hz***
VGB-1500	16.200.000	1921	1884,4	20000	68	Modularend	-	300	4,35	15	6,0	75	102,1	1:10	-	2272	80235	-	500	1640	NG**	3x575V/60Hz***
VGB-1500	17.500.000	2075	2035,6	22000	75	Modularend	-	300	4,35	15	6,0	90	122,5	1:12	-	2485	87757	-	501	1644	NG**	3x575V/60Hz***
VGB-1500	19.000.000	2253	2210,0	24000	82	Modularend	-	300	4,35	15	6,0	110	149,7	1:12	-	2898	99279	-	502	1647	NG**	3x575V/60Hz***
VGB-1500	21.500.000	2549	2501,0	27000	92	Modularend	-	300	4,35	15	6,0	132	179,7	1:12	-	3653	107816	-	503	1650	NG**	3x575V/60Hz***